



ACCELERATE YOUR CREATIVITY NVIDIA® QUADRO® K2200



Accelerate your creativity with NVIDIA® Quadro®—the world’s most powerful workstation graphics.

The NVIDIA Quadro K2200 delivers exceptional power-efficient 3D application performance. 4 GB of GDDR5 GPU memory with fast bandwidth enables you to create large, complex models, and a flexible single-slot form factor makes it compatible with even the most space and power-constrained chassis. Plus, an all-new display engine drives up to four displays with DisplayPort 1.2 support for ultra-high resolutions up to 3840x2160 @ 60 Hz with 30-bit color.

Quadro cards are certified with a broad range of sophisticated professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists, giving you the peace of mind to focus on doing your best work. Whether you’re developing revolutionary products or telling spectacularly vivid visual stories, Quadro gives you the performance to do it brilliantly.

THE PNY ADVANTAGE

PNY provides unsurpassed service and commitment to its professional graphics customers. In addition, PNY delivers a complete solution including the appropriate adapters, cables, brackets, driver software installation disc and documentation to ensure a quick and successful install.

FEATURES

- > Two DisplayPort 1.2 Connectors
- > DisplayPort with Audio
- > DVI-I Dual-Link Connector
- > VGA Support¹
- > NVIDIA nView™ Desktop Management Software Compatibility
- > HDCP Support
- > NVIDIA Mosaic²

PACKAGE CONTENTS

- > NVIDIA® Quadro® K2200 Professional Graphics Board
- > Software Installation Disc
- > Printed Quick Start Guide
- > DisplayPort to DVI-D SL Adapter
- > DVI to VGA Adapter

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



PNY PART NUMBER	VCQK2200-PB
SPECIFICATIONS	
GPU Memory	4 GB GDDR5
Memory Interface	128-bit
Memory Bandwidth	80.0 GB/s
NVIDIA CUDA Cores	640
System Interface	PCI Express 2.0 x16
Max Power Consumption	60 W
Thermal Solution	Ultra-Quiet Active Fansink
Form Factor	4.376" H x 7.97" L, Single Slot, Full Height
Display Connectors	DVI-I DL + 2x DP 1.2
Max Simultaneous Displays	3 Direct, 4 DP 1.2 Multi-Stream
Max DP 1.2 Resolution	3840 x 2160 at 60 Hz
Max DVI-I DL Resolution	2560 x 1600 at 60 Hz
Max DVI-I SL Resolution	1920 x 1200 at 60 Hz
Max VGA Resolution	2048 x 1536 at 85 Hz
Graphics APIs	Shader Model 5.0, OpenGL 4.5³, DirectX 11.2⁴
Compute APIs	CUDA, DirectCompute, OpenCL™

¹ Via supplied adapter/connector/bracket | ² Windows 7, 8, 8.1 and Linux | ³ Product is based on a published Khronos Specification, and is expected to pass the Khronos Conformance Testing Process when available. Current conformance status can be found at www.khronos.org/conformance | ⁴ GPU supports DX 11.2 API, Hardware Feature Level 11_0

© 2014 NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, CUDA, Kepler, and 3D Vision are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNY logotype is a registered trademark of PNY Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All other trademarks and copyrights are the property of their respective owners. JUL14



PNY Technologies, Inc.
100 Jefferson Road, Parsippany, NJ 07054
Tel 408 567 5500 | Fax 408 855 0680

For more information visit: www.pny.com/quadro