

MOBILE P4000 PRO PERFORMANCE, ANYTIME, ANYWHERE,





Introducing the PREVAILPRO P4000 from PNY, a powerful, lightweight and ultra-thin VR-Ready mobile workstation. Powered by NVIDIA® Quadro® P4000 GPU with Max-Q design, the PREVAILPRO P4000 features the workstation-class performance required to handle complex models or scenes, provide photorealistic rendering, and advanced display technologies to deliver the expansive visual workspace, or immersive VR experiences, that are increasingly required by demanding professional applications.

MODEL	UPGRADED PRO	
PART NUMBER	MWS-P4P-ENUSP-PB	
MEMORY	32GB (2× 16GB) DDR4 2400MHz SODIMM	
PRIMARY STORAGE	512GB M.2 2280 PCIe (Gen. 3 ×4) NVMe SSD	
SECONDARY STORAGE	2TB 2.5" Hard Disk Drive	
DISPLAY	15.6" UHD (3840 × 2160)	
ASPECT RATIO	16:9 Panel	
PROCESSOR	Intel® Core™ i7-7700HQ processor	
PROCESSOR SPEED	2.8GHz Base (Boost Up to 3.8GHz)	
PROCESSOR CACHE	6MB Smart Cache	
CORE LOGIC	Mobile Intel® HM175 Express Chipset	
MEMORY	Dual channel DDR4, supports up to 2400MHz Two 260 pin SODIMM sockets Expandable memory from 16GB to 32GB	
PROFESSIONAL GPU	NVIDIA Quadro Mobile P4000 • 8GB GDDR5 GPU Memory • OpenGL 4.5 • DirectX® 12 • Vulkan compatible • NVIDIA VRWorks™ • CUDA™, OpenCL, Direct • Compute compatible Microsoft Hybrid Graphics Mode • Supports 4 active displays	















FEATURES

KEYBOARD & POINTING DEVICE · English full size keyboard and numeric keypad with LED

backlighting · Touchpad with built in TPM fingerprint sensor

AUDIO

SOUND BLASTER® X-FI® MB5

- · High Definition Audio
- S/PDIF digital output
- · Built in array microphone
- · Built in dual speakers
- ANSP[™] 3D sound technology on headphone output

I/O PORTS

LEET:

- · Security lock slot
- · DC power connector
- . HDMI™ 2.0 with HDCP
- 2× Mini DisplayPort 1.3 ports
- 2× Type-C USB 3.1 Gen 2 ports
- 2× USB 3.1 Gen 1 ports RIGHT:
- 3.5mm 2-in-1 Audio Jack (Microphone S/PDIF optical output)
- USB 3.1 Gen 1 port
- · 6-in-1 Card Reader
- · RJ-45 LAN port

CARD READER

6-in-1 Card Reader Supports:

- · MMC / RSMMC
- · SD / mini SD / SDHC / SDXC up to UHS-II

COMMUNICATION

- · Built-in 10/100/1000 BASE-T Ethernet
- Intel® Dual Band Wireless-AC 8265, 2 × 2 AC + BT 4.2 M.2 2230 (Windstorm Peak)

2.0M FHD video camera

POWER SUPPLY

Full Range AC adapter, AC in 100~240V, 50~60Hz, DC output 19.5V, 7.7A, 150W

BATTERY

Embedded 4 cell Li-Polymer battery pack, 55WH; Battery life: 300 minutes (with UMA mode, 55WH battery)

SECURITY

- Kensington® Lock Slot
- Secure Touchpad with TPM 2.0 fingerprint scanner

OS SUPPORT (OPTIONAL)

Windows® 10 Pro 64-bit

LAPTOP DIMENSIONS

14.96" × 9.8" × 0.73" (380mm x 248mm x 18mm)

WEIGHT

4.8 Lbs. (2.2kg)

BIOS

- · 64Mb SPI Flash ROM
- · AMI BIOS

POWER MANAGEMENT

- · ACPI v5.0, Suspend to RAM (S3)
- · Suspend to disk (S4)
- · Soft off (S5)
- · Battery low suspend, Wake on LAN (S5)
- · Wake on USB (S3)
- · Wake on RTC alarm (S4)

LED INDICATORS

Power/Status, Battery, HDD, Airplane Mode, Camera

CERTIFICATES

FCC Class B, CE, cTUVus, TUV, CB. RoHS

ENVIRONMENTAL SPECIFICATIONS

Temperature:

- Operating: 5°C ~ 35°C
- Non-Operating: -20°C ~ 60°C

Relative Humidity:

- · Operating: 20% ~ 80%
- Non-Operating: 10% ~ 90%

Visit www.pny.com/mws-warranty for warranty details.

^{*} Features and specifications subject to change without notice.



MOBILE P3000

PRO PERFORMANCE, ANYTIME, ANYWHERE,



PNY PREVAILPRO P3000 series resets mobile workstation expectations by delivering the power and performance demanded by today's compute and graphics intensive professional applications in a lightweight and ultra-thin form factor. Powered by the NVIDIA Quadro P3000, the PREVAILPRO P3000 offers the ability to interactively work with large and complex models or scenes, drive up to four 4K UHD displays simultaneously and generate photorealistic renders on-the-go - all with unmatched NVIDIA Quadro performance, features and ISV compatibility.

MODEL	BASE	UPGRADED PRO
PART NUMBER	MWS-P3B-ENUSP1-PB	MWS-P3P-ENUSP-PB
MEMORY	16GB (2 × 8GB) DDR4 2400MHz SODIMM	32GB (2×16GB) DDR4 2400MHz SODIMM
PRIMARY STORAGE	128GB M.2 2280 PCIe (Gen. 3 × 4) NVMe SSD	512GB M.2 2280 PCIe (Gen 3 × 4) NVMe SSD
SECONDARY STORAGE	1TB 2.5" Hard Disk Drive	2TB 2.5" Hard Disk Drive
DISPLAY	15.6" FHD (1920 × 1080)	15.6" UHD (3840 × 2160)
ASPECT RATIO	16:9 Panel	16:9 Panel
PROCESSOR	Intel® Core™ i7-7700HQ processor	
PROCESSOR SPEED	2.8GHz Base (Boost Up to 3.8GHz)	
PROCESSOR CACHE	6MB Smart Cache	
CORE LOGIC	Mobile Intel® HM175 Express Chipset	
MEMORY	Dual channel DDR4, supports up to 2400MHz Two 260 pin SODIMM sockets Expandable memory from 16GB to 32GB	
	NVIDIA Quadro Mobile P3000 • 6GB GDDR5 GPU Memory • OpenGL 4.5 • DirectX® 12	
PROFESSIONAL GPU	 Vulkan compatible CUDA™, OpenCL, Direct Compute compatible Microsoft Hybrid Graphics Mode Supports 4 active displays 	

DVIDIA QUADRO









FEATURES

KEYBOARD & POINTING DEVICE

- · English full size keyboard and numeric keypad with LED backlighting
- · Touchpad with built in TPM fingerprint sensor

AUDIO

SOUND BLASTER® X-FI® MB5

- · High Definition Audio
- S/PDIF digital output
- · Built in array microphone
- · Built in dual speakers
- ANSP[™] 3D sound technology on headphone output

I/O PORTS

LEET:

- · Security lock slot
- · DC power connector
- . HDMI™ 2.0 with HDCP
- 2× Mini DisplayPort 1.3 ports
- 2× Type-C USB 3.1 Gen 2 ports
- 2× USB 3.1 Gen 1 ports

RIGHT:

- 3.5mm 2-in-1 Audio Jack (Microphone S/PDIF optical output)
- · USB 3.1 Gen 1 port
- · 6-in-1 Card Reader
- · RJ-45 LAN port

CARD READER

6-in-1 Card Reader Supports:

- · MMC / RSMMC
- SD / mini SD / SDHC / SDXC up to UHS-II

COMMUNICATION

- · Built-in 10/100/1000 BASE-T Ethernet
- Intel® Dual Band Wireless-AC 8265, 2 × 2 AC + BT 4.2 M.2 2230 (Windstorm Peak)

2.0M FHD video camera

POWER SUPPLY

Full Range AC adapter, AC in 100~240V, 50~60Hz, DC output 19.5V, 7.7A, 150W

BATTERY

Embedded 4 cell Li-Polymer battery pack, 55WH; Battery life: 300 minutes (with UMA mode, 55WH battery)

SECURITY

- Kensington® Lock Slot
- Secure Touchpad with TPM 2.0 fingerprint scanner

OS SUPPORT (OPTIONAL)

Windows® 10 Pro 64-bit

LAPTOP DIMENSIONS

14.96" × 9.8" × 0.73" (380mm x 248mm x 18mm)

WEIGHT

4.8 Lbs. (2.2kg)

BIOS

- · 64Mb SPI Flash ROM
- · AMI BIOS

POWER MANAGEMENT

- · ACPI v5.0, Suspend to RAM (S3)
- · Suspend to disk (S4)
- · Soft off (S5)
- · Battery low suspend, Wake on LAN (S5)
- · Wake on USB (S3)
- · Wake on RTC alarm (S4)

LED INDICATORS

Power/Status, Battery, HDD, Airplane Mode, Camera

CERTIFICATES

FCC Class B, CE, cTUVus, TUV, CB. RoHS

ENVIRONMENTAL SPECIFICATIONS

Temperature:

- Operating: 5°C ~ 35°C
- Non-Operating: -20°C ~ 60°C **Relative Humidity:**
- · Operating: 20% ~ 80%
- Non-Operating: 10% ~ 90%

^{*} Only available on MWS-P3P-ENUSP-PB