

Vertiv™ PowerUPS 200 Essential Line Interactive Series

Model Specifications Overview

Models	Power Rating	Input Voltage Range	Output Voltage Range	Height	Width	Depth	Weight
PSA6E-600IT-IEC	600VA / 315W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	180 mm	120 mm	355 mm	5.0 kg
PSA6E-1000IT-IEC	1000VA / 525W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	180 mm	120 mm	355 mm	6.2 kg
PSA6E-1600IT-IEC	1600VA / 925W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	195 mm	145 mm	400 mm	12.5 kg
PSA6E-2200IT-IEC	2200VA / 1225W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	195 mm	145 mm	400 mm	12.9 kg
PSA6E-600IT-SCH	600VA / 315W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	180 mm	120 mm	355 mm	5.0 kg
PSA6E-1000IT-SCH	1000VA / 525W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	180 mm	120 mm	355 mm	6.2 kg
PSA6E-1600IT-SCH	1600VA / 925W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	195 mm	145 mm	400 mm	12.5 kg
PSA6E-2200IT-SCH	2200VA / 1225W	Nominal: 220-240 VAC; Max: 140-290 VAC	On Utility: 220-240 VAC (Nominal); 195-255 VAC (Max) On Battery: 230 VAC (Nominal); 230 +/- 10 VAC (Max)	195 mm	145 mm	400 mm	12.9 kg