NVIDIA RTX™ 2000E Ada Generation







The NVIDIA RTX™ 2000E Ada Generation is a single-slot, power-efficient, compact GPU that brings the power of RTX into the reach of more professionals. With real-time ray tracing, Al-accelerated compute, and high-performance graphics, the RTX 2000E empowers users to tackle complex tasks, from content creation and design to data analysis and Al-driven applications, with incredible speed and precision.

Featuring the NVIDIA Ada Lovelace GPU architecture, it combines 22 third-generation RT Cores, 88 fourth-generation Tensor Cores, 2 816 CUDA® cores, and 16GB of GDDR6 graphics memory with ECC support. The RTX 2000E delivers breakthroughs in speed, efficiency, and power for everyday workflows, enabling creators, designers, and engineers to achieve new levels of productivity and innovation from the desktop.

NVIDIA RTX professional graphics cards are certified for a broad range of professional applications, tested by leading independent software vendors (ISVs) and workstation manufacturers, and backed by a global team of support specialists. Get the peace of mind to focus on what matters with the premier visual computing solution for mission-critical business.

KEY FEATURES

- ✓ Four Mini DisplayPort 1.4a
- AV1 encode and decode support
- ✓ DisplayPort with audio
- ✓ NVIDIA RTX Experience[™]
- ✓ NVIDIA RTX Desktop Manager software
- ✓ NVIDIA RTX IO support
- ✓ HDCP 2.2 support
- ✓ NVIDIA Mosaic¹ technology
- ✓ TDP 50W





PNY Power Limited

OPTIMIZED POWER, MAXIMUM EFFICIENCY

The NVIDIA RTX™ 2000E Power Limited by PNY is preset to a maximum power limit of 40 Watts, while the standard version has a power limit set at 50 Watts.

Whether you're worried about your carbon footprint, looking to take control of your total cost of ownership, or just need to reduce the Total Power Draw of your system, PNY's Power Limited GPU's are an excellent option.





PNY Part Numbers			
Part Number	EAN Code	MOQ*	Box Content (per card)
VCNRTX2000EADA-PL	3536403400934	5	1x LP Bracket
VCNRTX2000EADA-PLK	3536403600941	50	1x LP Bracket

SPECIFICATIONS			
Part Number	VCNRTX2000EADA-PL		
GPU memory	16 GB GDDR6		
Memory interface	128-bit		
Memory bandwidth	224 GB/s		
Error-correcting code (ECC)	Yes		
NVIDIA Ada Lovelace architecture- based CUDA Cores	2 816		
NVIDIA fourth-generation Tensor Cores	88		
NVIDIA third-generation RT Cores	22		
Single-precision performance	9,0 TFLOPS ²		
RT Core performance	20,7 TFLOPS ²		
Tensor performance	143,9 TFLOPS ³		
System interface	PCIe 4,0 x 8 ⁴		
Power consumption	50W - limited to 40W		
Thermal solution	Active		
Form factor	2,7" H x 6,6" L, Dual Slot		
Display connectors	4x Mini DisplayPort 1,4a		
	4x 4096 x 2160 @ 120 Hz		
Max simultaneous displays	4x 5120 x 2880 @ 60 Hz		
	2x 7680 x 4320 @ 60 Hz		
Encode/decode engines	1x encode, 1x decode (+AV1 encode and decode)		
VR-ready	Yes		
Graphics APIs	DirectX 12, Shader Model 6,6, OpenGL 4,6 ⁵ , Vulkan 1,3 ⁵		
Compute APIs	CUDA 11,6, OpenCL 3,0, DirectCompute		

Want to learn more about **PNY Power Limited Cards**?

Visit pny.com/en-eu/professional/power-limited-gpus

FOR MORE INFORMATION:

Contact your PNY representative or email PNYPRO@PNY.EU

PNY Technologies Europe, ZAC du Phare, 9 rue Joseph Cugnot, 33708 Mérignac cedex, France I Tel +33 (0)5 40 240 240 I WWW.PNY.EU

*MOQ - Multiple Order Quantity

¹Windows 10, 11, and Linux are supported. This configuration does not offer framelock synchronization or display overlap functionality. I ²Peak rates based on GPU Boost Clock. I ³ Effective FP8 teraFLOPS (TFLOPS) using the sparsity feature. I ⁴RTX 2000 Ada Generation utilizes a full-length PCle x8 interface. I ⁵ Product is based on a published Khronos specification and is expected to pass the Khronos conformance testing process when available. Current conformance status can be found at www.khronos.org/conformance

