



XLR8 Gaming MAKO RGB DDR5 5200MHz Desktop Memory



EPIC-X RGB™

Synchronize with mainstream motherboards and control your color experience.



Extreme Performance

Pushes the limit with aggressive speed, low latency, and extreme overclocking capabilities.



Intel XMP 3.0 Support

Super easy overclocking and runs at top speed.



Cool Under Pressure

Overclocking made simple for top speed performance.

THE NEXT EVOLUTION IN RGB PERFORMANCE

PNY XLR8 Gaming MAKO RGB DDR5 Memory is designed for gamers and enthusiasts offering the style and performance they crave while adding a brilliant RGB flair. The modules feature aluminum heat spreaders with elements inspired by the fast and aggressive Mako shark from which it gets its name. The MAKO name is proudly emblazoned alongside the XLR8 logo while angled silver relief lines machined into the heat spreader evoke shark imagery of gill slits. Compatibility with Intel XMP 3.0 delivers extreme overclocking out of the box and allows users to get the most out of their MAKO RGB DDR5 modules. Top-tier components and select ICs combine to deliver aggressive speed, low latency and the bullet-proof reliability gamers and enthusiasts can rely on PNY for.

For more than 35 years, PNY has been rigorously sourcing, testing, and manufacturing memory upgrades for thousands of the most popular PC platforms. Get your custom PC dressed and ready for battle with an XLR8 Gaming MAKO RGB DDR5 5200MHz CL38 upgrade from PNY and watch the world blaze.

DDR5 5200MHz PERFORMANCE

PNY's premium XLR8 memory features our most aggressive speeds, highest bandwidth, lowest latency and power consumption, and most advanced thermal performance for maximum PC stability and responsiveness during memory-intensive gaming and application use. XLR8 Gaming MAKO RGB DDR5 memory modules are rigorously engineered and tested to ensure peak performance in even the most challenging gaming environments.

PRODUCT SPECIFICATIONS

| | |
|-------------------------|---|
| Memory Type | DDR5 ECC Unbuffered DIMM |
| Capacity | 16GB, 32GB (2x16GB) |
| Channel Type | Dual Channel Modules Quad Channel Kits |
| Frequency Speed (JEDEC) | 5200MHz (PC5-41600) |
| CAS Latency | CL38 |
| Voltage | 1.2V |
| XMP 3.0 Support | Yes |
| Speed Compatibility | 5200MHz, 4800MHz |
| Warranty | Limited Lifetime |

PRODUCT INFORMATION

| | |
|-------------------|--|
| PNY Part Number | 16GB: MD16GSD5520038MXRGB 32GB (2x16GB): MD32GK2D5520038MXRGB |
| UPC | 16GB: 751492664873 32GB (2x16GB): 751492664880 |
| Module Dimensions | 5.25 x 1.61 inches |

