


NVIDIA IGX Thor Module and Boardkit

Enterprise-ready platform for physical AI.



NVIDIA IGX Thor Module and Boardkit

PNY Part Number: NVIGXTHOR7000-KIT

Server-Class Performance at Edge

The NVIDIA IGX Thor™ Platform unlocks real-time sensor processing and AI reasoning for physical AI agents with industrial-grade hardware, enterprise software, and functional safety. It's powered by the NVIDIA Blackwell architecture iGPU and an optional dGPU, delivering up to 5581 FP4 TFLOPS of AI compute to effortlessly run multiple generative AI models at the edge. Compared to NVIDIA IGX Orin™, it provides up to 8x higher AI compute on iGPU, 2.5x higher AI compute on dGPU, and 2x better connectivity.

NVIDIA IGX Thor offers two production-ready systems—the NVIDIA IGX™ T5000 module and the NVIDIA IGX T7000 board kit—built for diverse physical AI applications with functional safety. The IGX T5000 module features a Blackwell-powered iGPU, a 14-core Arm® Neoverse®-V3AE CPU, a suite of accelerators, and flexible I/O for customization. The IGX T7000 board kit is a complete system, featuring a module, a Board Management Controller (BMC), and an NVIDIA ConnectX®-7 SmartNIC with 400 GbE networking. You can also add an NVIDIA RTX PRO™ Blackwell dGPU—designed to accelerate customers' time-to-market. IGX Thor production systems use Transformer Engine and Multi-Instance GPU (MIG) support in the Blackwell architecture to deliver the performance to run multiple AI models with robust workload isolation. Functional Safety Island (FSI) inside the Thor SoC also enables advanced safety functions through the IGX software stack, ensuring reliable operation in mission-critical environments.

IGX Thor represents a new class of enterprise edge computers, purpose-built to power the next generation of industrial and medical edge applications. Leveraging the NVIDIA Blackwell GPU architecture, it excels at generative reasoning and multimodal sensor processing, supporting a broad range of generative AI models—from vision-language-action (VLA) models like NVIDIA Isaac™ GROOT N to popular LLMs and VLMs such as Cosmos™ Reason. To deliver a seamless cloud-to-edge experience, IGX Thor runs the NVIDIA AI Enterprise software stack and NVIDIA NIM™ for physical AI applications, including NVIDIA Isaac for robotics, NVIDIA Metropolis for visual AI agents, and NVIDIA Holoscan for sensor processing. Industrial safety AI agents can also be deployed at the edge using the NVIDIA Halos Outside-in Safety Agent Blueprint.

Our ecosystem of partners provides a complete range of carrier boards, design services, cameras, and sensors, along with AI and system software to speed solution development. They also support accelerating medical certifications (IEC 60601, 62304) and industrial functional safety certifications (ISO 26262, IEC 61508), helping you bring products to market faster and with confidence.

Key Features

NVIDIA IGX T5000 Module

- 2,560-core NVIDIA Blackwell architecture GPU with 96 fifth-generation Tensor Cores
- 14-core Arm® Neoverse®-V3AE 64-bit CPU
- 128 GB 256-bit LPDDR5X, 273 GB/s
- Functional Safety Island on the SOC
- Industrial-Grade Hardware

NVIDIA IGX T7000 Boardkit

- 2,560-core NVIDIA Blackwell architecture GPU with 96 fifth-generation Tensor Cores
- 14-core Arm Neoverse-V3AE 64-bit CPU
- 128 GB 256-bit LPDDR5X, 273 GB/s
- Options to add RTX PRO Blackwell dGPU to enhance AI performance
- ConnectX-7 SmartNIC with 400 GbE networking
- Board Management Controller
- Functional Safety Island on the SOC and Safety Microcontroller
- Industrial-Grade Hardware

With enterprise-level software, massive AI compute, and network security, IGX Thor is ideal for advancing medical imaging, surgical robotics, humanoid robotics, industrial AI automation, high-performance computing, and beyond. As an enterprise-ready platform, IGX Thor enables companies to focus on application development and accelerate the realization of AI's benefits.

Technical Specifications

NVIDIA IGX T5000		NVIDIA IGX T7000	
dGPU Option	—	With NVIDIA RTX Pro 6000 Blackwell Max-Q Workstation Edition	With NVIDIA RTX Pro Blackwell 5000
AI Performance	2,070 TFLOPS (FP4-Sparse)	Up to 5,581 TFLOPS (FP4-Sparse)	Up to 4,293 TFLOPS (FP4-Sparse)
iGPU	2,560-core NVIDIA Blackwell architecture GPU with 96 fifth-generation Tensor Cores Multi-Instance GPU with 10 TPCs	2,560-core NVIDIA Blackwell architecture GPU with 96 fifth-generation Tensor Cores Multi-Instance GPU with 10 TPCs	2,560-core NVIDIA Blackwell architecture GPU with 96 fifth-generation Tensor Cores Multi-Instance GPU with 10 TPCs
iGPU Max Frequency	1.57 GHz	1.57 GHz	1.57 GHz
dGPU	—	24,064-core Blackwell architecture GPU with fifth-generation Tensor Cores	14,080-core Blackwell architecture GPU with fifth-generation Tensor Cores
CPU	14-core Arm Neoverse-V3AE 64-bit CPU 64 KB I-cache, 64 KB dCache 1 MB L2 cache per core 16 MB shared system L3 cache	14-core Arm Neoverse-V3AE 64-bit CPU 64 KB I-cache, 64 KB dCache 1 MB L2 cache per core 16 MB shared system L3 cache	14-core Arm Neoverse-V3AE 64-bit CPU 64 KB I-cache, 64 KB dCache 1 MB L2 cache per core 16 MB shared system L3 cache
CPU Max Frequency	2.6 GHz	2.6 GHz	2.6 GHz
Vision Accelerator	1x PVA v3	1x PVA v3	1x PVA v3
Memory	128 GB 256-bit LPDDR5X 273 GB/s	128 GB 256-bit LPDDR5X 273 GB/s 96 GB dGPU memory 1,792 GB/s	128 GB 256-bit LPDDR5X 273 GB/s 48 GB dGPU memory 1,344 GB/s
Storage	Supports NVMe through PCIe Supports SSD through USB 3.2	4x SATA connectorsM.2 key M connector (PCIe Gen5 x2)	4x SATA connectorsM.2 key M connector (PCIe Gen5 x2)
Video Encode	2x NVEncode	2x NVEncode (iGPU) 4x NVEncode (dGPU)	2x NVEncode (iGPU) 3x NVEncode (dGPU)
Video Decode	2x NVDecode	2x NVDecode (iGPU) 4x NVDecode (dGPU)	2x NVDecode (iGPU) 3x NVDecode (dGPU)
PCIe	Up to 8 lanes: Gen5 Root port only: C1 (x1) and C3 (x2) Root point or endpoint: C2 (x1), C4 (x8), and C5 (x4)	2x PCIe Gen5 (x8, x16)	2x PCIe Gen5 (x8, x16)
USB	xHCI host controller with integrated PHY (up to) 3x USB 3.2 4x USB 2.0	1x USB 3.2 Type-C 4x USB 3.2 Type A	1x USB 3.2 Type-C 4x USB 3.2 Type A

Technical Specifications

NVIDIA IGX T5000		NVIDIA IGX T7000	
dGPU Option	–	With NVIDIA RTX Pro 6000 Blackwell Max-Q Workstation Edition	With NVIDIA RTX Pro Blackwell 5000
Networking	4x 25GbE	2x RJ45 (1GbE each) 2x QSFP28 (200GbE each)	2x RJ45 (1GbE each) 2x QSFP28 (200GbE each)
Integrated ConnectX	No	Yes	Yes
Display	1x shared HDMI 2.1 1x VESA DisplayPort 1.4a: HBR2, MST	1x VESA DisplayPort 1.4a	1x VESA DisplayPort 1.4a
Other I/O	2x 13-pin CAN header 2x 6-pin automation header 2x 5-pin header JTAG connector 1x 4-pin fan connector: 12V, PWM, and tach 2x 5-pin audio panel header 2-pin RTC backup battery connector	2x USB header for optional connection via cable 4x COM Ports 1x LPT 1x TPM 1x CAN 1x GPIO Audio Line-out, Mic In	2x USB header for optional connection via cable 4x COM Ports 1x LPT 1x TPM 1x CAN 1x GPIO Audio Line-out, Mic In
BMC	–	Yes	Yes
Safety Support	Functional Safety Island on SoC	Functional Safety Island on SoC Safety MCU on the carrier board	Functional Safety Island on SoC Safety MCU on the carrier board
NVIDIA AI Enterprise Support	Yes	Yes	Yes
Power	40 W-130 W Up to 300 W for dGPU	40 W-130 W TMP Up to 300 W for dGPU	40 W-130 W TMP Up to 300 W for dGPU
Mechanical	100 mm x 87 mm 699 pin B2B connector Integrated thermal transfer plate (TTP) with heat pipe	243.84 mm x 198.98 mm x 31.05 mm	243.84 mm x 198.98 mm x 31.05 mm

Ready to Get Started?

To learn more about the NVIDIA IGX Thor, visit
<https://www.pny.com/professional/hardware/nvidia-igx-thor>

© 2025 NVIDIA Corporation and affiliates. All rights reserved. NVIDIA, the NVIDIA logo, ConnectX, Cosmos, IGX, IGX Orin, IGX Thor, Isaac, NIM, and RTX PRO are trademarks and/or registered trademarks of NVIDIA Corporation and affiliates in the U.S. and other countries. Arm Neoverse is a registered trademark of Arm Limited (or its subsidiaries or affiliates) in the US and/or elsewhere. Other company and product names may be trademarks of the respective owners with which they are associated. 4387600. OCT25

