

Essential Professional Graphics For Maximum Productivity

The NVIDIA Quadro P400 combines a 256 CUDA core Pascal GPU, large on-board memory and advanced display technologies to deliver great performance for a range of professional applications. 2 GB of ultra-fast GPU memory makes it easy to manage complex 2D and 3D models and the single-slot, low-profile form factor makes it compatible with even the most space and power-constrained chassis. Support for three 4K displays (4096x2160 @ 60Hz) with HDR color gives you a wide visual workspace to view your work in extremely high resolution.

Quadro cards are certified with a broad range of sophisticated professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists, giving you the peace of mind to focus on doing your best work. Whether you're developing revolutionary products or telling spectacularly vivid visual stories, Quadro gives you the performance to do it brilliantly.

THE PNY ADVANTAGE

PNY provides unsurpassed service and commitment to its professional graphics customers. In addition, PNY delivers a complete solution including the appropriate adapters, cables, brackets, driver software installation disc and documentation to ensure a quick and successful install.

FEATURES

- Three mini DisplayPort 1.4 Connectors¹
- > DisplayPort with Audio
- » NVIDIA nView® Desktop Management Software
- > HDCP 2.2 Support
- > NVIDIA Mosaic²
- NVIDIA Iray and MentalRay Support

PACKAGE CONTENTS

- > NVIDIA® Quadro® P400 Professional Graphics Board
- > Aattached full-height (ATX) bracket
- > Unattached low-profile (SFF) bracket
- > Three mDP to DP adapters
- > Printed Quick Start Guide
- > Printed Support Guide

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



PNY PART NUMBER	VCQP400V2-PB
SPECIFICATIONS	
GPU Memory	2 GB GDDR5
Memory Interface	64-bit
Memory Bandwidth	Up to 32 GB/s
NVIDIA CUDA® Cores	256
System Interface	PCI Express 3.0 x16
Max Power Consumption	30 W
Thermal Solution	Active
Form Factor	2.713" H x 6.136" L, Single Slot, Low Profile
Display Connectors	3x mDP 1.4
Max Simultaneous Displays	3 direct, 3 DP 1.4 Multi-Stream
Display Resolution	3x 4096x2160 @ 60Hz 1x 5120x2880 @ 60Hz
Graphics APIs	Shader Model 5.1, OpenGL 4.5³, DirectX 12.0⁴, Vulkan 1.0³
Compute APIs	CUDA, DirectCompute, OpenCL™





¹ VGA/DVI/HDMI support via adapter/connector/bracket | ² Windows 7, 8, 8.1 and Linux | ³ Product is based on a published Khronos Specification, and is expected to pass the Khronos Conformance Testing Process when available. Current conformance status can be found at www.khronos.org/conformance | ⁴ GPU supports DX12.0 API, Hardware Feature Level 12_1

^{© 2021} NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, CUDA, NVIDIA Pascal, and 3D Vision are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNY logotype is a registered trademark of PNY Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All other trademarks and copyrights are the property of their respective owners. JUN21