



ACCELERATE YOUR CREATIVITY NVIDIA® QUADRO® K2200



Accelerate your creativity with NVIDIA® Quadro®—the world’s most powerful workstation graphics.

The NVIDIA Quadro K2200 delivers exceptional power-efficient 3D application performance. 4 GB of GDDR5 GPU memory with fast bandwidth enables you to create large, complex models, and a flexible single-slot form factor makes it compatible with even the most space and power-constrained chassis. Plus, an all-new display engine drives up to four displays with DisplayPort 1.2 support for ultra-high resolutions up to 3840x2160 @ 60 Hz with 30-bit color.

Quadro cards are certified with a broad range of sophisticated professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists, giving you the peace of mind to focus on doing your best work. Whether you’re developing revolutionary products or telling spectacularly vivid visual stories, Quadro gives you the performance to do it brilliantly.

THE PNY ADVANTAGE

PNY provides unsurpassed service and commitment to its professional graphics customers. In addition, PNY delivers a complete solution including the appropriate adapters, cables, brackets, driver software installation disc and documentation to ensure a quick and successful install.

FEATURES

- > Two DisplayPort 1.2 Connectors
- > DisplayPort with Audio
- > DVI-I Dual-Link Connector
- > VGA Support¹
- > NVIDIA nView™ Desktop Management Software Compatibility
- > HDCP Support
- > NVIDIA Mosaic²

PACKAGE CONTENTS

- > NVIDIA® Quadro® K2200 Professional Graphics Board
- > Software Installation Disc
- > Printed Quick Start Guide
- > DisplayPort to DVI-D SL Adapter
- > DVI to VGA Adapter

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



| PNY PART NUMBER | VCQK2200-PB |
|---------------------------|---|
| SPECIFICATIONS | |
| GPU Memory | 4 GB GDDR5 |
| Memory Interface | 128-bit |
| Memory Bandwidth | 80.0 GB/s |
| NVIDIA CUDA Cores | 640 |
| System Interface | PCI Express 2.0 x16 |
| Max Power Consumption | 68 W |
| Thermal Solution | Ultra-Quiet Active Fansink |
| Form Factor | 4.376" H x 7.97" L, Single Slot, Full Height |
| Display Connectors | DVI-I DL + 2x DP 1.2 |
| Max Simultaneous Displays | 3 Direct, 4 DP 1.2 Multi-Stream |
| Max DP 1.2 Resolution | 3840 x 2160 at 60 Hz |
| Max DVI-I DL Resolution | 2560 x 1600 at 60 Hz |
| Max DVI-I SL Resolution | 1920 x 1200 at 60 Hz |
| Max VGA Resolution | 2048 x 1536 at 85 Hz |
| Graphics APIs | Shader Model 5.0, OpenGL 4.5³, DirectX 11.2⁴ |
| Compute APIs | CUDA, DirectCompute, OpenCL™ |

¹ Via supplied adapter/connector/bracket | ² Windows 7, 8, 8.1 and Linux | ³ Product is based on a published Khronos Specification, and is expected to pass the Khronos Conformance Testing Process when available. Current conformance status can be found at www.khronos.org/conformance | ⁴ GPU supports DX 11.2 API, Hardware Feature Level 11_0

© 2014 NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, CUDA, Kepler, and 3D Vision are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNY logotype is a registered trademark of PNY Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All other trademarks and copyrights are the property of their respective owners. JUL14



PNY Technologies, Inc.
100 Jefferson Road, Parsippany, NJ 07054
Tel 408 567 5500 | Fax 408 855 0680

For more information visit: www.pny.com/quadro